



S3312SBV .3470434

SIZE (A)	DIMENSIONS					
	B	C	D	E	F	G
1/2"	.57"	2.26"	1.99"	.89"	.59"	3.5"

S3334SBV .3470435

SIZE (A)	DIMENSIONS					
	B	C	D	E	F	G
3/4"	.75"	2.81"	2.36"	1.18"	.79"	4.09"

S331SBV .3470436

SIZE (A)	DIMENSIONS					
	B	C	D	E	F	G
1"	.96"	3.46"	2.46"	1.42"	1.02"	4.63"

S33114SBV .3470437

SIZE (A)	DIMENSIONS					
	B	C	D	E	F	G
1-1/4"	1.26"	4.17"	2.76"	1.73"	1.18"	4.63"

S33112SBV .3470438

SIZE (A)	DIMENSIONS					
	B	C	D	E	F	G
1-1/2"	1.57"	4.57"	3.70"	1.97"	1.18"	5.71"

S332SBV .3470439

SIZE (A)	DIMENSIONS					
	B	C	D	E	F	G
2"	1.97"	5.35	4.02"	2.52"	1.38"	5.71"

MATERIAL SPECIFICATIONS		
1	Body	C46500
2	Bonnet	C46500
3	Seal	PTFE
4	Ball	C37700 (Chrome Plated)
5	Stem	C46500 (Copper Alloy Rod)
6	Seal Ring	PTFE
7	Stem Packing	PTFE
8	Gland Screw	C37700 (Copper Alloy Rod)
9	Handle	Steel (Zinc Plated)
10	Nut	C37700

Due to continuing product improvements, specifications may change without notice.

SUBMITTAL SHEET

PROJECT INFORMATION

Job Name:

Location:

Engineer:

Contractor:

P.O. Number:

Representative:

MODELS

☐ S3312SBV

☐ S3334SBV

☐ S331SBV

☐ S33114SBV

☐ S33112SBV

☐ S332SBV

DESCRIPTION

Stream33® C x C Full Port Ball Valve quarter-turn handle easily and quickly turns flow to the water supply on and off, making it simple to perform repairs or maintenance.

FEATURES

- Sweat x Sweat
- Cast Brass Body
- Lead Free

OPERATING SPECIFICATIONS

- Temperature rating: -30° - 200° F
- Pressure rating: 600 PSI maximum

APPROVALS

- FM Approved
- CSA
- UL

