



**S3312TBV** .3470424

SIZE (A)	DIMENSIONS					
	B	C	D	E	F	G
1/2" - 14NPT	.57"	2.24"	2.03"	.98"	.61"	3.5"

**S3334TBV** .3470427

SIZE (A)	DIMENSIONS					
	B	C	D	E	F	G
3/4" - 14NPT	.77"	2.48"	2.40"	1.22"	.63"	4.09"

**S331TBV** .3470429

SIZE (A)	DIMENSIONS					
	B	C	D	E	F	G
1" - 11.5NPT	.96"	2.97"	2.5"	1.5"	.75"	4.63"

**S33114TBV** .3470430

SIZE (A)	DIMENSIONS					
	B	C	D	E	F	G
1-1/4" - 11.5NPT	1.26"	3.4"	2.76"	1.85"	.77"	4.63"

**S33112TBV** .3470432

SIZE (A)	DIMENSIONS					
	B	C	D	E	F	G
1-1/2" - 11.5NPT	1.57"	3.70"	3.71"	2.09"	.77"	5.71"

**S332TBV** .3470433

SIZE (A)	DIMENSIONS					
	B	C	D	E	F	G
2" - 11.5NPT	1.97"	4.25"	4.02"	2.56"	.79"	5.71"

MATERIAL SPECIFICATIONS		
1	Body	C46500
2	Bonnet	C46500
3	Seal	PTFE
4	Ball	C37700 (Chrome Plated)
5	Stem	C46500 (Copper Alloy Rod)
6	Seal Ring	PTFE
7	Stem Packing	PTFE
8	Gland Screw	C37700 (Copper Alloy Rod)
9	Handle	Steel (Zinc Plated)
10	Nut	C37700

Due to continuing product improvements, specifications may change without notice.

## SUBMITTAL SHEET

### PROJECT INFORMATION

Job Name:

Location:

Engineer:

Contractor:

P.O. Number:

Representative:

### MODELS

☐ S3312TBV

☐ S3334TBV

☐ S331TBV

☐ S33114TBV

☐ S33112TBV

☐ S332TBV

### DESCRIPTION

Stream33® Threaded Full Port Ball Valve quarter-turn handle easily and quickly turns flow to the water supply on and off, making it simple to perform repairs or maintenance.

### FEATURES

- FNPT x FNPT

- Cast Brass Body

- Lead Free

### OPERATING SPECIFICATIONS

- Temperature rating: -30° - 200° F

- Pressure rating: 600 PSI maximum

### APPROVALS

- FM Approved

- CSA

- UL

