




Model	ID	Size
S3312BPMIP-PEXA	.3517618	1/2" x 1/2"
S3334BPMIP-PEXA	.3517619	3/4" x 3/4"
S331BPMIP-PEXA	.3517620	1" x 1"



Size	Inside Dia. (A)	Upper Barb Dia. (B)	Lower Barb Dia. (C)	End Length (D)
1/2"	0.378" min	0.618" min 0.61" max	0.579" min 0.571" max	0.689" min 0.729" max
3/4"	0.595" min	0.874" min 0.866" max	0.795" min 0.787" max	0.925" min 0.965" max
1"	0.795" min	1.11" min 1.102" max	1.032" min 1.024" max	1.161" min 1.201" max

SUBMITTAL SHEET

PROJECT INFORMATION

Job Name:

Location:

Engineer:

Contractor:

P.O. Number:

Representative:

MODELS

- ☐ S3312BPMIP-PEXA
 ☐ S331BPMIP-PEXA
 ☐ S3334BPMIP-PEXA

FEATURES

- C69300 (lead free) brass
- Manufactured to ASTM Standard F1960

OPERATING SPECIFICATIONS

- Can be used with PEX tubing manufactured to ASTM Standard F876
- Max pressure/temperature: 100 PSI at 180°F

APPROVALS

- NSF 14
- UPC
- Lead-free

RECOMMENDED ACCESSORIES

Model	ID	Description
S3312ER-PEXA	.3517626	1/2" Expansion Ring
S3334ER-PEXA	.3517627	3/4" Expansion Ring
S331ER-PEXA	.3517628	1" Expansion Ring