




Model	ID	Size
S3312BPMSW-PEXA	.3522498	1/2" x 1/2"
S3334BPMSW-PEXA	.3522499	3/4" x 3/4"



Size	Inside Dia. (A)	Upper Barb Dia.(B)	Lower Barb Dia. (C)	End Length (D)
1/2"	0.378" min	0.618" min 0.61" max	0.579" min 0.571" max	0.689" min 0.729" max
3/4"	0.595" min	0.874" min 0.866" max	0.795" min 0.787" max	0.925" min 0.965" max

SUBMITTAL SHEET

PROJECT INFORMATION

Job Name:

Location:

Engineer:

Contractor:

P.O. Number:

Representative:

MODELS

☐ S3312BPMSW-PEXA

☐ S3334BPMSW-PEXA

FEATURES

- C69300 (lead free) brass
- Manufactured to ASTM Standard F1960

OPERATING SPECIFICATIONS

- Can be used with PEX tubing manufactured to ASTM Standard F876
- Max pressure/temperature: 100 PSI at 180°F

APPROVALS

- NSF 14
- UPC
- Lead-free

RECOMMENDED ACCESSORIES

Model	ID	Description
S3312ER-PEXA	.3517626	1/2" Expansion Ring
S3334ER-PEXA	.3517627	3/4" Expansion Ring
S331ER-PEXA	.3517628	1" Expansion Ring