



FEATURES	Stream33 S33SP-13	Stream33 S33SP-12	Proven® BSP33 Series	Proven® BSP50 Series
Horsepower	1/3 HP	1/2 HP	1/3 HP	1/2 HP
Voltage	115 V	115 V	115 V	115 V
Amps	4.6 A	5.0 A	4.4 A	5.0 A
Motor	Oil-Filled Permanent Split Capacitor Motor	Oil-Filled Permanent Split Capacitor Motor	Oil-Filled Permanent Split Capacitor Motor	Oil-Filled Permanent Split Capacitor Motor
Max Head	26 ft.	28 ft.	25 ft.	28 ft.
Switch Type	Integrated Vertical Float	Integrated Vertical Float	Piggyback Vertical Float	Piggyback Vertical Float
Construction	Thermoplastic	Thermoplastic	Thermoplastic	Thermoplastic
Motor Protection	Automatic Thermal Overload Protector	Automatic Thermal Overload Protector	Automatic Thermal Overload Protector	Automatic Thermal Overload Protector
Corrosion Resistant	Yes	Yes	Yes	Yes
Finish	Black	Black	Black	Black
Height	10-15/16"	10-15/16"	12-1/5"	12-1/5"
Inlet	Top Suction with 1/8" Screen Opening	Top Suction with 1/8" Screen Opening	Top Suction with 1/8" Screen Opening	Top Suction with 1/8" Screen Opening
Discharge	1-1/2" FNPT with 1-1/4" Adapter	1-1/2" FNPT with 1-1/4" Adapter	1-1/2" FNPT with 1-1/4" Adapter	1-1/2" FNPT with 1-1/4" Adapter
Easy Access Handle	Yes	Yes	No	No
Safety Listing	UL Listed	UL Listed	CSA Listed	CSA Listed
Warranty	1 Year	1 Year	1 Year	1 Year