

SUBMITTAL SHEET

Project Information

Job Name: _____

Location: _____

Engineer: _____

Contractor: _____

P.O. Number: _____

Representative: _____



PEX-B x MIP PPSU MALE ADAPTER



Model	ID	Size
S3312PPMIP-PEXB	.3484306	1/2" x 1/2"
S331234PPMIP-PEXB	.3484307	1/2" x 3/4"
S3334PPMIP-PEXB	.3484308	3/4" x 3/4"
S331PPMIP-PEXB	.3484309	1" x 1"

PEX-B x FIP PPSU FEMALE ADAPTER



Model	ID	Size
S3312PPFIP-PEXB	.3484297	1/2" x 1/2"

PEX-B x PEX-B PPSU COUPLING



Model	ID	Size
S3312PPCOUP-PEXB	.3484292	1/2" x 1/2"
S333412PPCOUP-PEXB	.3484294	3/4" x 1/2"
S3334PPCOUP-PEXB	.3484293	3/4" x 3/4"
S33134PPCOUP-PEXB	.3484296	1" x 3/4"
S331PPCOUP-PEXB	.3484295	1" x 1"

PEX-B PPSU PLUG



Model	ID	Size
S3312PPLUG-PEXB	.3484298	1/2"
S3334PPLUG-PEXB	.3484299	3/4"
S331PPLUG-PEXB	.3484300	1"

FEATURES

- High performance PPSU plastic
- Manufactured to ASTM Standard F2159 and can be used with PEX tubing manufactured to ASTM Standard F876
- Max pressure/temperature: 100 PSI at 180° F
- Meets or exceeds the following:
 - NSF 14 & 61
 - UPC
 - Lead-free



INSTALLATION GUIDE

PPSU fittings should never be exposed to pipe dopes, glues or sealing adhesives, lubricants, or any other solvent. PPSU fittings should be stored and installed away from direct sunlight and other UV exposure. Complete installation instructions for PEX plumbing systems can be found at stream33.com.

SUBMITTAL SHEET

Project Information

Job Name: _____

Location: _____

Engineer: _____

Contractor: _____

P.O. Number: _____

Representative: _____



PEX-B x PEX-B x PEX-B PPSU TEE



Model	ID	Size
S3312PPTEE-PEXB	.3484310	1/2" x 1/2" x 1/2"
S33121234PPTEE-PEXB	.3484311	1/2" x 1/2" x 3/4"
S33341212PPTEE-PEXB	.3484312	3/4" x 1/2" x 1/2"
S33341234PPTEE-PEXB	.3484313	3/4" x 1/2" x 3/4"
S33343412PPTEE-PEXB	.3484315	3/4" x 3/4" x 1/2"
S3334PPTEE-PEXB	.3484316	3/4" x 3/4" x 3/4"
S3313434PPTEE-PEXB	.3484320	1" x 3/4" x 3/4"
S331112PPTEE-PEXB	.3484318	1" x 1" x 1/2"
S331134PPTEE-PEXB	.3484319	1" x 1" x 3/4"
S331PPTEE-PEXB	.3484317	1" x 1" x 1"

FEATURES

- High performance PPSU plastic
- Manufactured to ASTM Standard F2159 and can be used with PEX tubing manufactured to ASTM Standard F876
- Max pressure/temperature: 100 PSI at 180° F
- Meets or exceeds the following:
 - NSF 14 & 61
 - UPC
 - Lead-free



INSTALLATION GUIDE

PPSU fittings should never be exposed to pipe dopes, glues or sealing adhesives, lubricants, or any other solvent. PPSU fittings should be stored and installed away from direct sunlight and other UV exposure. Complete installation instructions for PEX plumbing systems can be found at stream33.com.

PEX-B x PEX-B PPSU ELBOW



Model	ID	Size
S3312PPELBOW-PEXB	.3484301	1/2" x 1/2"
S333412PPELBOW-PEXB	.3484303	3/4" x 1/2"
S3334PPELBOW-PEXB	.3484302	3/4" x 3/4"
S331PPELBOW-PEXB	.3484304	1" x 1"

PEX-B x PEX-B PPSU SWIVEL ELBOW



Model	ID	Size
S3312PPSFELBOW-PEXB	.3484305	1/2" x 1/2"