



FEATURES

- 3/4" male hose thread outlet
- 1/4 turn operation
- Auto draining if water is shut off and hose removed or open
- Heavy-duty rubberized handle
- Max. operating temp. rating: 140° F/60° C
- Max. operating pressure rating: 125 PSI
- Meets or exceeds the following:
 - ASME A112.18.1/CSA B125 standards
 - ASSE 1019-A standards



Model	Description	Connection Type	ID
S333420-3010	1/2" x 10"	Threaded	.3331294
S333420-3008	1/2" x 8"	Threaded	.3347094
S33FFSPEXA-8	1/2" x 8"	PEX-A	.3408277
S33FFSPEXB-8	1/2" x 8"	PEX-B	.3408278

WARRANTY

1-year warranty. Visit stream33.com for details.

PARTS AND MATERIALS



THREADED



PEX-A



PEX-B

Number	Description	Material
1	Handle bolt	Brass B124 C37700
2	Name plate	Aluminum A1100
3	Handwheel	Zinc (Z30A) 99.90-99.95%
4	Bonnet	Brass B16 C36000
5	Washer	Stainless steel 304/306
6	Packing	Rubber (NBR) SAE NO 1052#
7	Washer	Stainless steel 304/306
8	Stem pipe	Brass (copper alloy Nos. 27000)
9	Stem	Brass B16 C36000
10	Spring	Stainless steel 304/306
11	O-ring	Rubber (NBR) SAE NO 1052#
12	Spring seat	Brass B16 C36000
13	Packing	Rubber (NBR) SAE NO 1052#
14	Seat holder	Brass B124 C37700
15	Seat packing	Rubber (NBR) SAE NO 1052#
16	Seat screw	Brass B124 C37700
17	Body	Brass B584 C85710
18	Pipe flow	Brass (copper alloy Nos. 27000)
19	Nipple	Brass B16 C36000
20	Flange packing	Celcon M90 POM M90, CF500P
21	Floating	Celcon M90 POM M90, CF500P
22	Floating packing	Rubber (NBR) SAE NO 1052#
23	O-ring	Rubber (NBR) SAE NO 1052#
24	Bolt packing	Celcon M90 POM M90, CF500P
25	Cap	Brass B16 C36000

