



SUBMITTAL SHEET

Project Information

Job Name:

Location:

Engineer:

Contractor:

P.O. Number:

Representative:

Model	ID	Vol. (gal.) [Max. Vol.]	Ht.	Dia.	Conn. Size	Wt. (lbs)
S33HTX15	.3499215	2.1 [1]	12-1/2"	8"	1/2" MNPT	5.5
S33HTX30	.3499216	4.5 [2.5]	14"	11"		10
S33HTX60	.3499220	6 [3]	17-1/4"	11-1/2"		11.5
S33HTX90	.3499222	15 [6]	20-3/4"	16"	3/4" MNPT	28

FEATURES

- Diaphragm type hydropneumatic tank
- Designed for pressure control of residential and commercial hydronic heating systems
- Equipped with a pre-charged air chamber that allows for system water expansion
- Air charge is adjustable via charging valve located on top or bottom of the tank
- Temperature rating: 240° F maximum
- Pressure rating: 100 PSI maximum
- Adjustable factory preset pressure: 12 PSI
- Note: These tanks are not to be used on open or potable (domestic) water systems

WARRANTY

5-Year warranty. Visit stream33.com for details.

Material Specifications

Shell	Drawn Steel
Coating	Epoxy
Diaphragm	Butyl Rubber

SCHEDULE

Model	Tagging Information	Qty
S33HTX15		
S33HTX30		
S33HTX60		
S33HTX90		