



SUBMITTAL SHEET

Project Information

Job Name:

Location:

Engineer:

Contractor:

P.O. Number:

Representative:

Model	ID	Size (A)	Dimensions		
			B	C	D
S3312PBV	.3470521	1/2"	2.96"	1.77"	3.74"
S3334PBV	.3470530	3/4"	3.51"	1.93"	3.94"
S331PBV	.3470532	1"	3.71"	2.36"	4.33"
S33114PBV	.3470533	1-1/4"	4.57"	2.54"	5"
S33112PBV	.3470534	1-1/2"	5.47"	3.03"	6.18"
S332PBV	.3470537	2"	6.69"	3.46"	6.18"

Part #	Material Specification	
1	Body	C46500
2	Caps	C46500
3	Ball Seat	PTFE
4	Ball	C46500 or Stainless steel
5	Stem	HPb59
6	O-Ring	EPDM
7	Gland Gasket	PTFE
8	Gland	HPb59
9	Handle	Q235+PVC
10	Washer	Stainless steel
11	Nut	Stainless steel
12	O-Ring	EPDM

FEATURES

- Press end connections
- Two-piece, lead-free brass body
- Quarter-turn handle for quick and easy flow
- Max. pressure rating: 250 CWP
- Max. temperature rating: 250°F @ 225psig
- Meets or exceeds the following:
 - NSF 61/372
 - cUPC
 - MSS SP-145



WARRANTY

1-Year warranty. Visit stream33.com for details.

