



## SUBMITTAL SHEET

### Project Information

Job Name:

Location:

Engineer:

Contractor:

P.O. Number:

Representative:

Model	ID	Size (A)	Dimensions					
			B	C	D	E	F	G
S3312SBV	.3470434	1/2"	0.57"	2.26"	1.99"	0.89"	0.59"	3.5"
S3334SBV	.3470435	3/4"	0.75"	2.81"	2.36"	1.18"	0.79"	4.09"
S331SBV	.3470436	1"	0.96"	3.46"	2.46"	1.42"	1.02"	4.63"
S33114SBV	.3470437	1-1/4"	1.26"	4.17"	2.76"	1.73"	1.18"	4.63"
S33112SBV	.3470438	1-1/2"	1.57"	4.57"	3.7"	1.97"	1.18"	5.71"
S332SBV	.3470439	2"	1.97"	5.35"	4.02"	2.52"	1.38"	5.71"

### FEATURES

- Sweat end connections
- Two-piece, lead-free brass body
- Quarter-turn handle for quick and easy operation
- Full port design for improved flow characteristics
- Max. pressure rating: 600PSI WOG
- Max. temperature rating: 250°F
- Meets or exceeds the following:
  - FM
  - UL

Part #	Material Specification	
1	Body	Lead-free Brass
2	Bonnet	Lead-free Brass
3	Seal	PFTE
4	Ball	C37700 (Chrome Plated)
5	Stem	C46500 (Copper Alloy Rod)
6	Seal Ring	PFTE
7	Stem Packing	PFTE
8	Screw	C37700 (Copper Alloy Rod)
9	Handle	Steel (Zinc Plated)
10	Nut	C37700

### WARRANTY

1-Year warranty. Visit [stream33.com](http://stream33.com) for details.

